

Specifications



Product model	TJ420L	TJ430L	TJ630L	TJ650L
Sensor				
Type	Uncooled VOx Infrared Detector, 8 to 14 μm			
Resolution	400×300@12μm		640×512@12μm	
NETD	25mK		20mK	
Frame rate	50Hz			
Lens				
Objective lens	25mm, F1.0	35mm, F1.0		50mm, F1.0
Field of view	11.0°×8.2°	7.9°×5.9°	12.5°×9.4°	8.8°×6.6°
FOV m @100m	19×14	14×10	22×16	15×12
Magnification	3.04x~12.16x	4.25x~17.0x	2.66x~21.28x	3.79x~30.32x
Detection range	1000m/yd	1400m/yd		2000m/yd
Display				
Display type	0.39" AMOLED 1920x1080			
Color palettes	White Hot, Black Hot, Red Hot, Green Hot, Iron Red, Blue Hot, Sepia			
Eyepiece	Exit pupil distance 16 mm; Diopter: -6 to +6; Zoom: 18x			
Hardware				
Laser rangefinder	1000m/yd			
WIFI	2.4G, 5G			
Interface	USB Type-C (Power supply/USB2.0)			
Others	Microphone, Compass, Gyroscope, Bluetooth			
System				
Recording function	Photo/Video (Audio recording included)			
Memory capacity	32GB		64GB	
Power				
Battery type	2 replaceable 18650 batteries			
Operating time	12 hours		10 hours	
Environmental				
Operating temp.	-20 °C to 50 °C/ -4°F to +122°F			
Encapsulation	IP67			
Physical				
Weight(g/ oz)	558/ 19.68	583/ 20.56	581/ 20.49	625/ 22.05
Size(mm/ in)	234×97×66/ 9.21×3.82×2.60	243×97×66/ 9.57×3.82×2.60	234×97×66/ 9.21×3.82×2.60	243×97×66/ 9.57×3.82×2.60
Standard	A device, Wrist strap, Battery charger, 18650 battery×2, 5V2A adapter (US, Britain, Australia and Europe), USB Type-C cable, Quick use guide, Warranty card			
Optional	Bluetooth remote control, 18650 battery			